

**SL1818/1120-E-TB**

Cylindrical roller bearing

Cylindrical roller bearing, SL1818..-E-TB
full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Technical information



Your current product variant

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	1.120 mm	Bore diameter
D	1.360 mm	Outside diameter
B	106 mm	Width
C_r	3.350.000 N	Basic dynamic load rating, radial
C_{0r}	8.500.000 N	Basic static load rating, radial
C_{ur}	620.000 N	Fatigue load limit, radial
n_G	235 1/min	Limiting speed
n_{gr}	119 1/min	Reference speed
m	306,3 kg	Weight





Mounting dimensions

$d_{a \min}$	1.204 mm	Minimum diameter shaft shoulder
$d_{c \min}$	1.204 mm	Minimum shaft shoulder
$D_{a \max}$	1.273,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	1.297 mm	Minimum diameter of housing shoulder
$r_{a \max}$	6 mm	Maximum recess radius
E	1.297 mm	Raceway diameter outer ring

Dimensions

r_{\min}	6 mm	Minimum chamfer dimension
s	13,9 mm	Axial displacement
d_1	1.204 mm	Maximum rib diameter inner ring
$D_1 \min$	1.273,5 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing