

**SL1818/530-E-TB-BR-IR/T-CN/3L**

Cylindrical roller bearing

Cylindrical roller bearing, SL1818..-E-TB
full complement roller set, single row, semi-
locating bearing, 1 rib on outer ring, 2 ribs on
inner ring, type SL18

Technical information



Your current product variant

Design	TB	Bearings with increased axial load capacity
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	530 mm	Bore diameter
D	650 mm	Outside diameter
B	56 mm	Width
C_r	1.010.000 N	Basic dynamic load rating, radial
C_{0r}	2.170.000 N	Basic static load rating, radial
C_{ur}	208.000 N	Fatigue load limit, radial
n_G	510 1/min	Limiting speed
n_{gr}	320 1/min	Reference speed
m	36,6 kg	Weight





Mounting dimensions

$d_{a \min}$	573 mm	Minimum diameter shaft shoulder
$d_{c \min}$	573 mm	Minimum shaft shoulder
$D_{a \max}$	611 mm	Maximum diameter of housing shoulder
$D_{e \min}$	625,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
E	625,5 mm	Raceway diameter outer ring

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
d_1	573 mm	Maximum rib diameter inner ring
$D_1 \min$	611,1 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing