

**SL182232-A-BR-C3**

Cylindrical roller bearing

Cylindrical roller bearing SL1822..-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	80 mm	Width
C_r	1.020.000 N	Basic dynamic load rating, radial
C_{0r}	1.470.000 N	Basic static load rating, radial
C_{ur}	187.000 N	Fatigue load limit, radial
n_G	1.370 1/min	Limiting speed
n_{gr}	920 1/min	Reference speed
m	22.63 kg	Weight





Mounting dimensions

$d_{a \min}$	208,7 mm	Minimum diameter shaft shoulder
$d_{c \min}$	208,5 mm	Minimum shaft shoulder
$D_{a \max}$	253 mm	Maximum diameter of housing shoulder
$D_{e \min}$	267 mm	Minimum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
E	267,1 mm	Raceway diameter outer ring

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
s	6 mm	Axial displacement
d_1	208,7 mm	Maximum rib diameter inner ring
$D_1 \min$	253,4 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed