

**SL182217**

## Cylindrical roller bearing

Cylindrical roller bearing SL1822..-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

## Technical information



## Your current product variant

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	36 mm	Width
$C_r$	255.000 N	Basic dynamic load rating, radial
$C_{0r}$	320.000 N	Basic static load rating, radial
$C_{ur}$	47.500 N	Fatigue load limit, radial
$n_G$	2.850 1/min	Limiting speed
$n_{gr}$	2.000 1/min	Reference speed
$m$	2,648 kg	Weight





### Mounting dimensions

$d_{a \min}$	104,5 mm	Minimum diameter shaft shoulder
$d_{c \min}$	104 mm	Minimum shaft shoulder
$D_{a \max}$	126 mm	Maximum diameter of housing shoulder
$D_{e \min}$	133,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum recess radius
E	133,8 mm	Raceway diameter outer ring


### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
s	1,5 mm	Axial displacement
$d_1$	104,4 mm	Maximum rib diameter inner ring
$D_1 \min$	126,3 mm	Minimum rib diameter outer ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed