

**SL183016-A**

Cylindrical roller bearing

Cylindrical roller bearing SL18..-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	125 mm	Outside diameter
B	34 mm	Width
C_r	170.000 N	Basic dynamic load rating, radial
C_{0r}	220.000 N	Basic static load rating, radial
C_{ur}	33.000 N	Fatigue load limit, radial
n_G	3.200 1/min	Limiting speed
n_{gr}	2.470 1/min	Reference speed
m	1,392 kg	Weight





Mounting dimensions

$d_{a \min}$	95 mm	Minimum diameter shaft shoulder
$d_{c \min}$	95 mm	Minimum shaft shoulder
$D_{a \max}$	111,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	117 mm	Minimum diameter of housing shoulder
$r_{a \max}$	1,1 mm	Maximum recess radius
E	117,4 mm	Raceway diameter outer ring


Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
s	4 mm	Axial displacement
d_1	95 mm	Maximum rib diameter inner ring
$D_1 \min$	111,7 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed