

**SL183020-A-C3**

Cylindrical roller bearing

Cylindrical roller bearing SL18..-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	150 mm	Outside diameter
B	37 mm	Width
C_r	216.000 N	Basic dynamic load rating, radial
C_{0r}	300.000 N	Basic static load rating, radial
C_{ur}	43.500 N	Fatigue load limit, radial
n_G	2.600 1/min	Limiting speed
n_{gr}	2.040 1/min	Reference speed
m	2,079 kg	Weight





Mounting dimensions

$d_{a \min}$	115,7 mm	Minimum diameter shaft shoulder
$d_{c \min}$	115,5 mm	Minimum shaft shoulder
$D_{a \max}$	134 mm	Maximum diameter of housing shoulder
$D_{e \min}$	140 mm	Minimum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum recess radius
E	140,2 mm	Raceway diameter outer ring






Dimensions

r_{\min}	1,5 mm	Minimum chamfer dimension
s	4 mm	Axial displacement
d_1	115,7 mm	Maximum rib diameter inner ring
$D_1 \min$	134 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed