

**SL183034-A-C3**

## Cylindrical roller bearing

Cylindrical roller bearing SL18...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

## Technical information



## Your current product variant

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	170 mm	Bore diameter
D	260 mm	Outside diameter
B	67 mm	Width
$C_r$	700.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.050.000 N	Basic static load rating, radial
$C_{ur}$	135.000 N	Fatigue load limit, radial
$n_G$	1.480 1/min	Limiting speed
$n_{gr}$	1.120 1/min	Reference speed
$m$	11,776 kg	Weight





### Mounting dimensions

$d_{a \min}$	198,1 mm	Minimum diameter shaft shoulder
$d_{c \min}$	198 mm	Minimum shaft shoulder
$D_{a \max}$	232,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	243,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
E	243,6 mm	Raceway diameter outer ring

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
s	7 mm	Axial displacement
$d_1$	198,1 mm	Maximum rib diameter inner ring
$D_1 \min$	232,7 mm	Minimum rib diameter outer ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed