**SL183088-A-C3**

Cylindrical roller bearing

Cylindrical roller bearing SL18..-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	440 mm	Bore diameter
D	650 mm	Outside diameter
B	157 mm	Width
C_r	3.700.000 N	Basic dynamic load rating, radial
C_{0r}	6.500.000 N	Basic static load rating, radial
C_{ur}	600.000 N	Fatigue load limit, radial
n_G	560 1/min	Limiting speed
n_{gr}	295 1/min	Reference speed
m	163,38 kg	Weight





Mounting dimensions

$d_{a \min}$	503 mm	Minimum diameter shaft shoulder
$d_{c \min}$	503 mm	Minimum shaft shoulder
$D_{a \max}$	584 mm	Maximum diameter of housing shoulder
$D_{e \min}$	584 mm	Minimum diameter of housing shoulder
$r_{a \max}$	6 mm	Maximum recess radius
E	611,4 mm	Raceway diameter outer ring






Dimensions

r_{\min}	6 mm	Minimum chamfer dimension
s	18 mm	Axial displacement
d_1	503 mm	Maximum rib diameter inner ring
$D_1 \min$	584 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed