

**SL192315**

Cylindrical roller bearing

Technical information



Your current product variant

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	160 mm	Outside diameter
B	55 mm	Width
C_r	405.000 N	Basic dynamic load rating, radial
C_{0r}	465.000 N	Basic static load rating, radial
C_{ur}	72.000 N	Fatigue load limit, radial
n_G	2.800 1/min	Limiting speed
n_{gr}	2.000 1/min	Reference speed
m	5,205 kg	Weight






Dimensions

D_1	131,5 mm	Shoulder diameter outer ring
$D_{a \max}$	131,5 mm	Maximum diameter of housing shoulder
d_1	101,6 mm	Shoulder diameter inner ring
$d_{a \min}$	91 mm	Minimum diameter shaft shoulder
$d_{c \min}$	101,5 mm	Minimum shaft shoulder
F	92,2 mm	Raceway diameter inner ring
$r_{a \max}$	2,1 mm	Maximum fillet radius
r_{\min}	2,1 mm	Minimum chamfer dimension
s	3,5 mm	Axial displacement

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed