


**SL192317-C3**

Cylindrical roller bearing

Technical information

**Your current product variant**

Number of rolling element rows	1	Single-row design
--------------------------------	---	-------------------

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	180 mm	Outside diameter
B	60 mm	Width
C_r	500.000 N	Basic dynamic load rating, radial
C_{0r}	610.000 N	Basic static load rating, radial
C_{ur}	88.000 N	Fatigue load limit, radial
n_G	2.410 1/min	Limiting speed
n_{gr}	1.710 1/min	Reference speed
$\approx m$	7,144 kg	Weight



Dimensions

D ₁	150,9 mm	Shoulder diameter outer ring
D _{a max}	150,5 mm	Maximum diameter of housing shoulder
d ₁	118,2 mm	Shoulder diameter inner ring
d _{a min}	107 mm	Minimum diameter shaft shoulder
d _{c min}	118 mm	Minimum shaft shoulder
F	107 mm	Raceway diameter inner ring
r _{a max}	3 mm	Maximum fillet radius
r _{min}	3 mm	Minimum chamfer dimension
s	4 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed