


**SL192318-TB-XL-C3**

## Cylindrical roller bearing

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

## Technical information



## Your current product variant

Number of rows	1	Single-row design
----------------	---	-------------------

## Main Dimensions &amp; Performance Data

d	90 mm	Bore diameter
D	190 mm	Outside diameter
B	64 mm	Width
$C_r$	620.000 N	Basic dynamic load rating, radial
$C_{0r}$	650.000 N	Basic static load rating, radial
$C_{ur}$	118.000 N	Fatigue load limit, radial
$n_G$	2.750 1/min	Limiting speed
$n_{gr}$	1.760 1/min	Reference speed
$m$	8,61 kg	Weight








## Dimensions

$D_1$	152,5 mm	Shoulder diameter outer ring
$D_{a \max}$	152,5 mm	Maximum diameter of housing shoulder
$d_1$	117,5 mm	Shoulder diameter inner ring
$d_{a \min}$	105 mm	Minimum diameter shaft shoulder
$d_{c \min}$	117,5 mm	Minimum shaft shoulder
F	105,3 mm	Raceway diameter inner ring
$r_{a \max}$	3 mm	Maximum fillet radius
$r_{\min}$	3 mm	Minimum chamfer dimension
s	4 mm	Axial displacement

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

## Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed