

**SL192340-TB-BR**

## Cylindrical roller bearing

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

## Technical information



## Your current product variant

Number of rolling element rows	1	Single-row design
--------------------------------	---	-------------------

## Main Dimensions &amp; Performance Data

d	200 mm	Bore diameter
D	420 mm	Outside diameter
B	138 mm	Width
$C_r$	2.470.000 N	Basic dynamic load rating, radial
$C_{0r}$	3.300.000 N	Basic static load rating, radial
$C_{ur}$	350.000 N	Fatigue load limit, radial
$n_G$	1.020 1/min	Limiting speed
$n_{gr}$	570 1/min	Reference speed
$m$	90,3 kg	Weight









## Dimensions

$D_1$	347,2 mm	Shoulder diameter outer ring
$D_{a \max}$	347 mm	Maximum diameter of housing shoulder
$d_1$	265,7 mm	Shoulder diameter inner ring
$d_{a \min}$	238 mm	Minimum diameter shaft shoulder
$d_{c \min}$	265,5 mm	Minimum shaft shoulder
F	238,5 mm	Raceway diameter inner ring
$r_{a \max}$	5 mm	Maximum fillet radius
$r_{\min}$	5 mm	Minimum chamfer dimension
s	7 mm	Axial displacement

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

## Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing