

**SL192348-TB-BR**

Cylindrical roller bearing

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

Technical information



Your current product variant

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	500 mm	Outside diameter
B	155 mm	Width
C _r	2.900.000 N	Basic dynamic load rating, radial
C _{0r}	3.800.000 N	Basic static load rating, radial
C _{ur}	390.000 N	Fatigue load limit, radial
n _G	860 1/min	Limiting speed
n _{gr}	500 1/min	Reference speed
m	139,6 kg	Weight









Dimensions

D_1	408,5 mm	Shoulder diameter outer ring
$D_{a \max}$	408,5 mm	Maximum diameter of housing shoulder
d_1	312,5 mm	Shoulder diameter inner ring
$d_{a \min}$	280,5 mm	Minimum diameter shaft shoulder
$d_{c \min}$	312,5 mm	Minimum shaft shoulder
F	280,6 mm	Raceway diameter inner ring
$r_{a \max}$	5 mm	Maximum fillet radius
r_{\min}	5 mm	Minimum chamfer dimension
s	10 mm	Axial displacement

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing