


**RSL182305-A**

Cylindrical roller bearing



Cylindrical roller bearing RSL1823, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Technical information



Your current product variant

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	25 mm	Bore diameter
E _w	53,72 mm	Outer envelope circle
B	24 mm	Width
C _r	64.000 N	Basic dynamic load rating, radial
C _{0r}	59.000 N	Basic static load rating, radial
C _{ur}	7.800 N	Fatigue load limit, radial
n _G	8.100 1/min	Limiting speed
≈m	0,208 kg	Weight

Mounting dimensions

d _{a min}	34,5 mm	Minimum diameter shaft shoulder
X	15 mm	Raceway width








Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
d_1	34,6 mm	Maximum rib diameter inner ring
T_K	42,72 mm	Pitch circle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed