

**RSL182313-A**

Cylindrical roller bearing



Cylindrical roller bearing RSL1823, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Technical information

**Your current product variant**

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	65 mm	Bore diameter
E _w	126,69 mm	Outer envelope circle
B	48 mm	Width
C _r	310.000 N	Basic dynamic load rating, radial
C _{0r}	345.000 N	Basic static load rating, radial
C _{ur}	55.000 N	Fatigue load limit, radial
n _G	3.200 1/min	Limiting speed
≈m	2,356 kg	Weight

Mounting dimensions

d _{a min}	90 mm	Minimum diameter shaft shoulder
X	22 mm	Raceway width








Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
d_1	90 mm	Maximum rib diameter inner ring
T_K	103,69 mm	Pitch circle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed