

**RSL182326-A** [↗](#)

Cylindrical roller bearing



Cylindrical roller bearing RSL1823, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Technical information



Your current product variant

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	130 mm	Bore diameter
E _w	247,9 mm	Outer envelope circle
B	93 mm	Width
C _r	1.110.000 N	Basic dynamic load rating, radial
C _{0r}	1.380.000 N	Basic static load rating, radial
C _{ur}	184.000 N	Fatigue load limit, radial
n _G	1.570 1/min	Limiting speed
≈m	17,8 kg	Weight

Mounting dimensions

d _{a min}	176 mm	Minimum diameter shaft shoulder
X	68 mm	Raceway width




Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
d_1	176 mm	Maximum rib diameter inner ring
T_K	202,9 mm	Pitch circle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics



Radial load



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed