

**RSL182330-A**

## Cylindrical roller bearing



Cylindrical roller bearing RSL1823, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

## Technical information

**Your current product variant**

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

**Main Dimensions & Performance Data**

d	150 mm	Bore diameter
E <sub>w</sub>	286,49 mm	Outer envelope circle
B	108 mm	Width
C <sub>r</sub>	1.490.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.900.000 N	Basic static load rating, radial
C <sub>ur</sub>	220.000 N	Fatigue load limit, radial
n <sub>G</sub>	1.350 1/min	Limiting speed
≈m	26,953 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	203,3 mm	Minimum diameter shaft shoulder
X	80 mm	Raceway width



### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$d_1$	203,3 mm	Maximum rib diameter inner ring
$T_K$	234,49 mm	Pitch circle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed