


**RSL183032-A**

Cylindrical roller bearing



Cylindrical roller bearing RSL1830, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Technical information



Your current product variant

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
E _w	224,8 mm	Outer envelope circle
B	60 mm	Width
C _r	540.000 N	Basic dynamic load rating, radial
C _{0r}	800.000 N	Basic static load rating, radial
C _{ur}	105.000 N	Fatigue load limit, radial
n _G	1.600 1/min	Limiting speed
≈m	5,764 kg	Weight

Mounting dimensions

d _{a min}	185 mm	Minimum diameter shaft shoulder
X	36 mm	Raceway width








Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
d_1	185 mm	Maximum rib diameter inner ring
T_K	199,8 mm	Pitch circle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed