

**RSL182213-A-XL**


## Cylindrical roller bearing



Cylindrical roller bearing RSL18.-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

X-life

## Technical information



## Your current product variant

Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	65 mm	Bore diameter
E <sub>w</sub>	106,25 mm	Outer envelope circle
B	31 mm	Width
C <sub>r</sub>	198.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	210.000 N	Basic static load rating, radial
C <sub>ur</sub>	39.500 N	Fatigue load limit, radial
n <sub>G</sub>	4.200 1/min	Limiting speed
≈m	0,925 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	82,3 mm	Minimum diameter shaft shoulder
X	22 mm	Raceway width

## Dimensions





r <sub>min</sub>	1,5 mm	Minimum chamfer dimension
d <sub>1</sub>	82,3 mm	Maximum rib diameter inner ring
T <sub>K</sub>	91,25 mm	Pitch circle



### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed