

**RSL183004-A-XL**


Cylindrical roller bearing



Cylindrical roller bearing RSL1830..-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

X-life

Technical information



Your current product variant

Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	20 mm	Bore diameter
E _w	36,81 mm	Outer envelope circle
B	16 mm	Width
C _r	30.500 N	Basic dynamic load rating, radial
C _{0r}	26.000 N	Basic static load rating, radial
C _{ur}	4.550 N	Fatigue load limit, radial
n _G	13.100 1/min	Limiting speed
≈m	63 g	Weight

Mounting dimensions

d _{a min}	28,8 mm	Minimum diameter shaft shoulder
X	9 mm	Raceway width

Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
d ₁	28,8 mm	Maximum rib diameter inner ring
T _K	30,81 mm	Pitch circle



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics



Radial load



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed