

**RSL183008-A-XL**

Cylindrical roller bearing

Cylindrical roller bearing RSL1830..-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

X-life

Technical information



Your current product variant

Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
E _w	61,74 mm	Outer envelope circle
B	21 mm	Width
C _r	66.000 N	Basic dynamic load rating, radial
C _{0r}	67.000 N	Basic static load rating, radial
C _{ur}	11.400 N	Fatigue load limit, radial
n _G	7.300 1/min	Limiting speed
≈m	0,191 kg	Weight

Mounting dimensions

d _{a min}	50,5 mm	Minimum diameter shaft shoulder
X	12 mm	Raceway width








Dimensions

r_{min}	1 mm	Minimum chamfer dimension
d_1	50,5 mm	Maximum rib diameter inner ring
T_K	53,74 mm	Pitch circle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  F_a Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed