

**RSL182314-A-2S**

Cylindrical roller bearing



Cylindrical roller bearing RSL1823, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Technical information

**Your current product variant**

Design	A	Internal Variant Cage A
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	70 mm	Bore diameter
E _w	132,14 mm	Outer envelope circle
B	51 mm	Width
C _r	340.000 N	Basic dynamic load rating, radial
C _{0r}	385.000 N	Basic static load rating, radial
C _{ur}	60.000 N	Fatigue load limit, radial
n _G	3.050 1/min	Limiting speed
≈m	2,594 kg	Weight

Mounting dimensions

d _{a min}	94 mm	Minimum diameter shaft shoulder
X	36 mm	Raceway width

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
d ₁	94 mm	Maximum rib diameter inner ring
T _K	108,14 mm	Pitch circle



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics



Radial load



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed