


**RSL183017-A-3S**

Cylindrical roller bearing



Cylindrical roller bearing RSL1830, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Technical information



Your current product variant

Design	A	Internal Variant Cage A
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	85 mm	Bore diameter
E _w	121,44 mm	Outer envelope circle
B	34 mm	Width
C _r	175.000 N	Basic dynamic load rating, radial
C _{0r}	231.000 N	Basic static load rating, radial
C _{ur}	34.500 N	Fatigue load limit, radial
n _G	3.050 1/min	Limiting speed
≈m	0,999 kg	Weight

Mounting dimensions

d _{a min}	99,5 mm	Minimum diameter shaft shoulder
X	20 mm	Raceway width

Dimensions






r _{min}	1,1 mm	Minimum chamfer dimension
d ₁	99,5 mm	Maximum rib diameter inner ring
T _K	107,44 mm	Pitch circle



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed