**SL024892**

Cylindrical roller bearing

Cylindrical roller bearing SL02, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	460 mm	Bore diameter
D	580 mm	Outside diameter
B	118 mm	Width
C_r	1.570.000 N	Basic dynamic load rating, radial
C_{0r}	4.500.000 N	Basic static load rating, radial
C_{ur}	450.000 N	Fatigue load limit, radial
n_G	580 1/min	Limiting speed
n_{gr}	310 1/min	Reference speed
m	75,9 kg	Weight

Mounting dimensions

$d_{c \text{ min}}$	507 mm	Minimum shaft shoulder
$d_{a \text{ min}}$	506,4 mm	Minimum diameter shaft shoulder
$D_{e \text{ min}}$	539,5 mm	Minimum diameter of housing shoulder
$r_{a \text{ max}}$	4 mm	Maximum recess radius



Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
s	6 mm	Axial displacement
C	59 mm	Distance to lubrication hole
$d_{1 \max}$	506,4 mm	Maximum rib diameter inner ring
E	544,6 mm	Raceway diameter outer ring





Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

NNCL4880V	Bearing designation DIN5412
-----------	-----------------------------

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed