


**SL024896**

Cylindrical roller bearing

Cylindrical roller bearing SL02, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	480 mm	Bore diameter
D	600 mm	Outside diameter
B	118 mm	Width
C_r	1.610.000 N	Basic dynamic load rating, radial
C_{0r}	4.750.000 N	Basic static load rating, radial
C_{ur}	465.000 N	Fatigue load limit, radial
n_G	560 1/min	Limiting speed
n_{gr}	290 1/min	Reference speed
m	76,853 kg	Weight

Mounting dimensions

$d_{c \min}$	530 mm	Minimum shaft shoulder
$d_{a \min}$	529,6 mm	Minimum diameter shaft shoulder
$D_{e \min}$	557,35 mm	Minimum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius



Dimensions

r_{min}	4 mm	Minimum chamfer dimension
s	7 mm	Axial displacement
C	59 mm	Distance to lubrication hole
$d_{1 max}$	529,6 mm	Maximum rib diameter inner ring
E	597,55 mm	Raceway diameter outer ring





Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

NNCL4896V	Bearing designation DIN5412
-----------	-----------------------------

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed