


**SL024916**

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	110 mm	Outside diameter
B	30 mm	Width
C_r	112.000 N	Basic dynamic load rating, radial
C_{0r}	206.000 N	Basic static load rating, radial
C_{ur}	30.500 N	Fatigue load limit, radial
n_G	3.550 1/min	Limiting speed
n_{gr}	2.090 1/min	Reference speed
m	0,843 kg	Weight

Mounting dimensions

$d_{c \min}$	91,5 mm	Minimum shaft shoulder
$d_{a \min}$	91,4 mm	Minimum diameter shaft shoulder
$D_{e \min}$	100,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum recess radius



Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
C	15 mm	Distance to lubrication hole
$d_{1 \max}$	91,4 mm	Maximum rib diameter inner ring
E	100,78 mm	Raceway diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

NNCL4916V

Bearing designation DIN5412

Characteristics



Radial load



Grease Lubrication



Oil Lubrication



Not sealed