

**SL024916-A-C3**

## Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

## Technical information



## Your current product variant

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

## Main Dimensions &amp; Performance Data

d	80 mm	Bore diameter
D	110 mm	Outside diameter
B	30 mm	Width
C <sub>r</sub>	112.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	206.000 N	Basic static load rating, radial
C <sub>ur</sub>	30.500 N	Fatigue load limit, radial
n <sub>G</sub>	3.550 1/min	Limiting speed
n <sub>gr</sub>	2.090 1/min	Reference speed
m	0,843 kg	Weight

## Mounting dimensions

d <sub>c min</sub>	91,5 mm	Minimum shaft shoulder
d <sub>a min</sub>	91,4 mm	Minimum diameter shaft shoulder
D <sub>e min</sub>	100,5 mm	Minimum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum recess radius



### Dimensions

r <sub>min</sub>	1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
C	15 mm	Distance to lubrication hole
d <sub>1 max</sub>	91,4 mm	Maximum rib diameter inner ring
E	100,78 mm	Raceway diameter outer ring





### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

NNCL4916V	Bearing designation DIN5412
-----------	-----------------------------

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed