

**SL024932**

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	220 mm	Outside diameter
B	60 mm	Width
C_r	425.000 N	Basic dynamic load rating, radial
C_{0r}	880.000 N	Basic static load rating, radial
C_{ur}	111.000 N	Fatigue load limit, radial
n_G	1.660 1/min	Limiting speed
n_{gr}	1.080 1/min	Reference speed
m	6,578 kg	Weight

Mounting dimensions

$d_{c \min}$	184,5 mm	Minimum shaft shoulder
$d_{a \min}$	184,2 mm	Minimum diameter shaft shoulder
$D_{e \min}$	206 mm	Minimum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum recess radius



Dimensions

r _{min}	2 mm	Minimum chamfer dimension
s	4 mm	Axial displacement
C	30 mm	Distance to lubrication hole
d _{1 max}	184,2 mm	Maximum rib diameter inner ring
E	206,16 mm	Raceway diameter outer ring





Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

NNCL4932V	Bearing designation DIN5412
-----------	-----------------------------

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed