

**SL024976**

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

| | | |
|---------------------------|--------------|---------------------------|
| Design | A | Internal Variant A |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Number of rows | 2 | Double-row design |

Main Dimensions & Performance Data

| | | |
|----------|-------------|-----------------------------------|
| d | 380 mm | Bore diameter |
| D | 520 mm | Outside diameter |
| B | 140 mm | Width |
| C_r | 2.250.000 N | Basic dynamic load rating, radial |
| C_{0r} | 5.500.000 N | Basic static load rating, radial |
| C_{ur} | 590.000 N | Fatigue load limit, radial |
| n_G | 680 1/min | Limiting speed |
| n_{gr} | 325 1/min | Reference speed |
| m | 90,5 kg | Weight |

Mounting dimensions

| | | |
|--------------|----------|--------------------------------------|
| $d_{c \min}$ | 430,5 mm | Minimum shaft shoulder |
| $d_{a \min}$ | 430,2 mm | Minimum diameter shaft shoulder |
| $D_{e \min}$ | 481 mm | Minimum diameter of housing shoulder |
| $r_{a \max}$ | 4 mm | Maximum recess radius |



Dimensions

| | | |
|--------------|-----------|---------------------------------|
| r_{\min} | 4 mm | Minimum chamfer dimension |
| s | 7 mm | Axial displacement |
| C | 70 mm | Distance to lubrication hole |
| $d_{1 \max}$ | 430,2 mm | Maximum rib diameter inner ring |
| E | 481,35 mm | Raceway diameter outer ring |

Temperature range






| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Additional information

NNCL4976V

Bearing designation DIN5412

Characteristics

| | |
|---|--------------------|
|  | Radial load |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |
|  | Large bearing |