

**SL024996-A-C3**

## Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

## Technical information



## Your current product variant

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

## Main Dimensions &amp; Performance Data

d	480 mm	Bore diameter
D	650 mm	Outside diameter
B	170 mm	Width
$C_r$	3.450.000 N	Basic dynamic load rating, radial
$C_{0r}$	8.800.000 N	Basic static load rating, radial
$C_{ur}$	870.000 N	Fatigue load limit, radial
$n_G$	540 1/min	Limiting speed
$n_{gr}$	227 1/min	Reference speed
$m$	162,77 kg	Weight

## Mounting dimensions

$d_{c \min}$	537,5 mm	Minimum shaft shoulder
$d_{a \min}$	537,4 mm	Minimum diameter shaft shoulder
$D_{e \min}$	601,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum recess radius



### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
s	8,5 mm	Axial displacement
C	85 mm	Distance to lubrication hole
$d_{1 \max}$	537,4 mm	Maximum rib diameter inner ring
E	601,4 mm	Raceway diameter outer ring





### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

NNCL4972V	Bearing designation DIN5412
-----------	-----------------------------

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed