

**SL184926-A-C3** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing SL18..-A, full complement roller set, two-row, semi-locating bearing, 1 rib on outer ring, 3 ribs on inner ring, type SL18

Technical information

Your current product variant

| | | |
|---------------------------|--------------|-----------------------------------|
| Design | A | Internal Variant A |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Number of rows | 2 | Double-row design |

Main Dimensions & Performance Data

| | | |
|----------|-------------|-----------------------------------|
| d | 130 mm | Bore diameter |
| D | 180 mm | Outside diameter |
| B | 50 mm | Width |
| C_r | 260.000 N | Basic dynamic load rating, radial |
| C_{0r} | 510.000 N | Basic static load rating, radial |
| C_{ur} | 64.000 N | Fatigue load limit, radial |
| n_G | 2.090 1/min | Limiting speed |
| n_{gr} | 1.500 1/min | Reference speed |
| m | 3,819 kg | Weight |



Mounting dimensions

| | | |
|---------------|----------|--------------------------------------|
| $d_{c \min}$ | 148 mm | Minimum shaft shoulder |
| $d_{a \min}$ | 148,4 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 159,7 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,1 mm | Maximum recess radius |
| $r_{a1 \max}$ | 1,5 mm | Maximum recess radius |
| $D_{e \min}$ | 159,7 mm | Minimum diameter of housing shoulder |

Dimensions

| | | |
|--------------|----------|---------------------------------|
| r_{\min} | 1,5 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1,5 mm | Minimum chamfer dimension |
| s | 2 mm | Axial displacement |
| C | 25 mm | Distance to lubrication hole |
| d_1 | 148,4 mm | Maximum rib diameter inner ring |
| $D_1 \min$ | 159,7 mm | Minimum rib diameter outer ring |
| E | 165,4 mm | Raceway diameter outer ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Characteristics

| | |
|-------------------------------------------------------------------------------------|-----------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |