

**SL184932-A** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing SL18..-A, full complement roller set, two-row, semi-locating bearing, 1 rib on outer ring, 3 ribs on inner ring, type SL18

## Technical information

**Your current product variant**

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

**Main Dimensions & Performance Data**

d	160 mm	Bore diameter
D	220 mm	Outside diameter
B	60 mm	Width
$C_r$	425.000 N	Basic dynamic load rating, radial
$C_{0r}$	880.000 N	Basic static load rating, radial
$C_{ur}$	111.000 N	Fatigue load limit, radial
$n_G$	1.660 1/min	Limiting speed
$n_{gr}$	1.080 1/min	Reference speed
$m$	6,664 kg	Weight



### Mounting dimensions

$d_{c \text{ min}}$	184 mm	Minimum shaft shoulder
$d_{a \text{ min}}$	184,2 mm	Minimum diameter shaft shoulder
$D_{a \text{ max}}$	200 mm	Maximum diameter of housing shoulder
$r_{a \text{ max}}$	2 mm	Maximum recess radius
$r_{a1 \text{ max}}$	2 mm	Maximum recess radius
$D_{e \text{ min}}$	200 mm	Minimum diameter of housing shoulder

### Dimensions

$r_{\text{min}}$	2 mm	Minimum chamfer dimension
$r_{1 \text{ min}}$	2 mm	Minimum chamfer dimension
$s$	2 mm	Axial displacement
$C$	30 mm	Distance to lubrication hole
$d_1$	184,2 mm	Maximum rib diameter inner ring
$D_1 \text{ min}$	200 mm	Minimum rib diameter outer ring
$E$	206,16 mm	Raceway diameter outer ring

### Temperature range

$T_{\text{min}}$	-30 °C	Operating temperature min.
$T_{\text{max}}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed