

**SL184976-A-C3** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing SL18..-A, full complement roller set, two-row, semi-locating bearing, 1 rib on outer ring, 3 ribs on inner ring, type SL18

## Technical information

**Your current product variant**

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

**Main Dimensions & Performance Data**

d	380 mm	Bore diameter
D	520 mm	Outside diameter
B	140 mm	Width
$C_r$	2.250.000 N	Basic dynamic load rating, radial
$C_{0r}$	5.500.000 N	Basic static load rating, radial
$C_{ur}$	590.000 N	Fatigue load limit, radial
$n_G$	680 1/min	Limiting speed
$n_{gr}$	325 1/min	Reference speed
$m$	88,75 kg	Weight



### Mounting dimensions

$d_{c \min}$	430,5 mm	Minimum shaft shoulder
$d_{a \min}$	430,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	467,5 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$r_{a1 \max}$	4 mm	Maximum recess radius
$D_{e \min}$	468 mm	Minimum diameter of housing shoulder

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$r_{1 \min}$	4 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
C	70 mm	Distance to lubrication hole
$d_1$	430,2 mm	Maximum rib diameter inner ring
$D_1 \min$	468 mm	Minimum rib diameter outer ring
E	481,35 mm	Raceway diameter outer ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed