

**SL014934-A-C3**

Cylindrical roller bearing

Cylindrical roller bearings SL0149, locating bearing, double row, full complement cylindrical roller set, dimension series 49

Technical information



Your current product variant

Design	A	Internal Variant Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	230 mm	Outside diameter
B	60 mm	Width
C _r	435.000 N	Basic dynamic load rating, radial
C _{0r}	930.000 N	Basic static load rating, radial
C _{ur}	115.000 N	Fatigue load limit, radial
n _G	1.580 1/min	Limiting speed
n _{gr}	1.010 1/min	Reference speed
m	7,03 kg	Weight

Mounting dimensions

r _{a max}	2 mm	Maximum recess radius
d _{a min}	193,1 mm	Minimum diameter shaft shoulder
D _{a max}	209,5 mm	Maximum diameter of housing shoulder



Dimensions

r_{min}	2 mm	Minimum chamfer dimension
d_1	193,1 mm	Maximum rib diameter inner ring
$D_1 min$	209,1 mm	Minimum rib diameter outer ring
$d_{c min}$	193 mm	Minimum shaft shoulder
C	30 mm	Distance to lubrication hole







Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

NNC4934V	Bearing designation DIN5412
----------	-----------------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed