

**SL014948-A-C3**

Cylindrical roller bearing

Cylindrical roller bearings SL0149, locating bearing, double row, full complement cylindrical roller set, dimension series 49

Technical information



Your current product variant

Design	A	Internal Variant Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	320 mm	Outside diameter
B	80 mm	Width
C_r	740.000 N	Basic dynamic load rating, radial
C_{0r}	1.700.000 N	Basic static load rating, radial
C_{ur}	198.000 N	Fatigue load limit, radial
n_G	1.110 1/min	Limiting speed
n_{gr}	660 1/min	Reference speed
m	17,66 kg	Weight

Mounting dimensions

$r_{a \max}$	2,1 mm	Maximum recess radius
$d_{a \min}$	270,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	292,5 mm	Maximum diameter of housing shoulder



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
d_1	270,6 mm	Maximum rib diameter inner ring
$D_1 \min$	292,3 mm	Minimum rib diameter outer ring
$d_{c \min}$	270,5 mm	Minimum shaft shoulder
C	40 mm	Distance to lubrication hole

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

NNC4948V

Bearing designation DIN5412

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing