

**SL014840**

Cylindrical roller bearing

Cylindrical roller bearings, locating bearing, double row, full complement cylindrical roller set, dimension series 48

Technical information



Your current product variant

Design	A	Internal Variant Cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	250 mm	Outside diameter
B	50 mm	Width
C_r	320.000 N	Basic dynamic load rating, radial
C_{0r}	770.000 N	Basic static load rating, radial
C_{ur}	86.000 N	Fatigue load limit, radial
n_G	1.410 1/min	Limiting speed
n_{gr}	960 1/min	Reference speed
m	5,424 kg	Weight

Mounting dimensions

$r_{a \max}$	1,5 mm	Maximum recess radius
$d_{a \min}$	218,1 mm	Minimum diameter shaft shoulder
$D_{a \max}$	231,5 mm	Maximum diameter of housing shoulder



Dimensions

r_{min}	1,5 mm	Minimum chamfer dimension
d_1	218,1 mm	Maximum rib diameter inner ring
$D_1 min$	231,2 mm	Minimum rib diameter outer ring
$d_{c min}$	218 mm	Minimum shaft shoulder
C	25 mm	Distance to lubrication hole

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

NNC4840V

Bearing designation DIN5412

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed