


**SL014914-A-C3**

Cylindrical roller bearing

Cylindrical roller bearings SL0149, locating bearing, double row, full complement cylindrical roller set, dimension series 49

Technical information



Your current product variant

Design	A	Internal Variant Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	100 mm	Outside diameter
B	30 mm	Width
C_r	106.000 N	Basic dynamic load rating, radial
C_{0r}	185.000 N	Basic static load rating, radial
C_{ur}	27.500 N	Fatigue load limit, radial
n_G	3.900 1/min	Limiting speed
n_{gr}	2.330 1/min	Reference speed
m	0,767 kg	Weight

Mounting dimensions

$r_{a \max}$	1 mm	Maximum recess radius
$d_{a \min}$	82,5 mm	Minimum diameter shaft shoulder
$D_{a \max}$	87,5 mm	Maximum diameter of housing shoulder



Dimensions

r_{min}	1 mm	Minimum chamfer dimension
d_1	82,5 mm	Maximum rib diameter inner ring
$D_1 min$	87,4 mm	Minimum rib diameter outer ring
$d_{c min}$	82,5 mm	Minimum shaft shoulder
C	15 mm	Distance to lubrication hole

Temperature range







T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

NNC4914V

Bearing designation DIN5412

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed