

**SL045036-D-PP-C3**

## Cylindrical roller bearing

Cylindrical roller bearing SL04...-D-PP, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

## Technical information



## Your current product variant

Design	D	New outer Contour
Type of Seal	PP	Contact Seal on both sides
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

## Main Dimensions &amp; Performance Data

d	180 mm	Bore diameter
D	280 mm	Outside diameter
B	136 mm	Width
$C_r$	1.140.000 N	Basic dynamic load rating, radial
$C_{0r}$	2.130.000 N	Basic static load rating, radial
$C_{ur}$	270.000 N	Fatigue load limit, radial
$n_G$ Grease	680 1/min	Limiting speed for grease lubrication
$\approx m$	29,22 kg	Weight



### Mounting dimensions

C <sub>a1</sub>	110 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C <sub>a2</sub>	108 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d <sub>1</sub>	218 mm	Rib diameter inner ring
d <sub>2</sub>	239 mm	Sealing diameter (rib)
d <sub>3</sub>	302 mm	Outside diameter of snap ring WRE
d <sub>1 min</sub>	218 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

### Dimensions

C	135 mm	Width, outer ring
C <sub>1</sub>	118,2 mm	Distance ring grooves
D <sub>1</sub>	274 mm	Diameter of groove
m	5,2 mm	Width of groove
r <sub>min</sub>	0,6 mm	Minimum chamfer dimension
t	2 mm	Chamfer width
X	112 mm	Distance between rolling elements

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	80 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides