

**SL04220-D-PP-RR-C5-GA22** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing SL04...-D-PP, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

## Technical information



## Your current product variant

Design	D	New outer Contour
Sealing	PP	Contact Seal on both sides
Radial internal clearance	C5 (Group 5)	Internal clearance larger than C4
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

## Main Dimensions &amp; Performance Data

d	220 mm	Bore diameter
D	300 mm	Outside diameter
B	95 mm	Width
$C_r$	700.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.550.000 N	Basic static load rating, radial
$C_{ur}$	185.000 N	Fatigue load limit, radial
$n_G$ Grease	610 1/min	Limiting speed for grease lubrication
$\approx m$	18,422 kg	Weight



### Mounting dimensions

C <sub>a1</sub>	75 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C <sub>a2</sub>	73 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d <sub>1</sub>	249 mm	Rib diameter inner ring
d <sub>2</sub>	264 mm	Sealing diameter (rib)
d <sub>3</sub>	322 mm	Outside diameter of snap ring WRE
d <sub>1 min</sub>	249 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

### Dimensions

C	94 mm	Width, outer ring
C <sub>1</sub>	83,2 mm	Distance ring grooves
D <sub>1</sub>	294 mm	Diameter of groove
m	5,2 mm	Width of groove
r <sub>min</sub>	1 mm	Minimum chamfer dimension
t	2 mm	Chamfer width
X	72 mm	Distance between rolling elements

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	80 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides