

**SL045008-PP-2NR-C3-L091** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing SL04...-PP-2NR, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

## Technical information

**Your current product variant**

Sealing	PP	Contact Seal on both sides
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	38 mm	Width
C <sub>r</sub>	80.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	111.000 N	Basic static load rating, radial
C <sub>ur</sub>	16.300 N	Fatigue load limit, radial
n <sub>G</sub> Grease	3.150 1/min	Limiting speed for grease lubrication
≈m	0,555 kg	Weight



### Mounting dimensions

C <sub>a1</sub>	28 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C <sub>a2</sub>	27 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d <sub>1</sub>	51,5 mm	Rib diameter inner ring
d <sub>2</sub>	55 mm	Sealing diameter (rib)
d <sub>3</sub>	75 mm	Outside diameter of snap ring WRE
d <sub>1 min</sub>	51,5 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

### Dimensions

C	37 mm	Width, outer ring
C <sub>1</sub>	32,2 mm	Distance ring grooves
D <sub>1</sub>	65,8 mm	Diameter of groove
m	2,7 mm	Width of groove
r <sub>min</sub>	0,6 mm	Minimum chamfer dimension
t	0,8 mm	Chamfer width
X	28,5 mm	Distance between rolling elements

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	80 °C	Operating temperature max.