

**RSL185011-A** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, two-row, semi-locating bearing, no outer ring, 3 ribs on inner ring, type RSL18

## Technical information



## Your current product variant

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

## Main Dimensions &amp; Performance Data

d	55 mm	Rib diameter inner ring
E <sub>w</sub>	83,54 mm	Outer envelope circle
B	46 mm	Width
C <sub>r</sub>	182.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	275.000 N	Basic static load rating, radial
C <sub>ur</sub>	37.000 N	Fatigue load limit, radial
n <sub>G</sub>	4.550 1/min	Limiting speed
n <sub>gr</sub>	2.950 1/min	Reference speed
m	0,821 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	68,5 mm	Minimum diameter shaft shoulder
--------------------	---------	---------------------------------

## Dimensions

r <sub>min</sub>	1,1 mm	Minimum chamfer dimension
X	39 mm	Raceway width



### Temperature range

---

$T_{min}$  -30 °C Operating temperature min.

$T_{max}$  120 °C Operating temperature max.

### Characteristics

---



Radial load



Grease Lubrication



Oil Lubrication



Not sealed