


**RSL185012-A** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, two-row, semi-locating bearing, no outer ring, 3 ribs on inner ring, type RSL18

Technical information

**Your current product variant**

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (PN)
Number of rolling element rows	2	Double-row design

Main Dimensions & Performance Data

d	60 mm	Rib diameter inner ring
E _w	86,74 mm	Outer envelope circle
B	46 mm	Width
C _r	187.000 N	Basic dynamic load rating, radial
C _{0r}	285.000 N	Basic static load rating, radial
C _{ur}	39.000 N	Fatigue load limit, radial
n _G	4.350 1/min	Limiting speed
n _{gr}	2.750 1/min	Reference speed
≈m	0,795 kg	Weight

Mounting dimensions

d _{a min}	71,5 mm	Minimum diameter shaft shoulder
--------------------	---------	---------------------------------

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
X	39 mm	Raceway width



Temperature range

T_{min} -30 °C Operating temperature min.

T_{max} 120 °C Operating temperature max.

Characteristics



Radial load



Grease Lubrication



Oil Lubrication



Not sealed