

**RSL185015-A** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, two-row, semi-locating bearing, no outer ring, 3 ribs on inner ring, type RSL18

## Technical information



## Your current product variant

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

## Main Dimensions &amp; Performance Data

d	75 mm	Rib diameter inner ring
E <sub>w</sub>	107,9 mm	Outer envelope circle
B	54 mm	Width
C <sub>r</sub>	245.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	385.000 N	Basic static load rating, radial
C <sub>ur</sub>	54.000 N	Fatigue load limit, radial
n <sub>G</sub>	3.450 1/min	Limiting speed
n <sub>gr</sub>	2.400 1/min	Reference speed
m	1,361 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	89 mm	Minimum diameter shaft shoulder
--------------------	-------	---------------------------------

## Dimensions

r <sub>min</sub>	1,1 mm	Minimum chamfer dimension
X	42 mm	Raceway width



### Temperature range

---

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Characteristics

---

-   $F_r$  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed