

**RSL185030-A**

Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, two-row, semi-locating bearing, no outer ring, 3 ribs on inner ring, type RSL18

Technical information



Your current product variant

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	150 mm	Rib diameter inner ring
E _w	206,8 mm	Outer envelope circle
B	100 mm	Width
C _r	810.000 N	Basic dynamic load rating, radial
C _{0r}	1.390.000 N	Basic static load rating, radial
C _{ur}	186.000 N	Fatigue load limit, radial
n _G	1.740 1/min	Limiting speed
n _{gr}	1.150 1/min	Reference speed
m	8,184 kg	Weight

Mounting dimensions

d _{a min}	170,5 mm	Minimum diameter shaft shoulder
--------------------	----------	---------------------------------

Dimensions





r _{min}	2,1 mm	Minimum chamfer dimension
X	80 mm	Raceway width



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed