

**HK2526-L271** [↗](#)

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end  
HK, single row, with cage

## Technical information



## Your current product variant

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	Without	

## Main Dimensions &amp; Performance Data

$F_w$	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	26 mm	Width
$C_r$	25.500 N	Basic dynamic load rating, radial
$C_{0r}$	45.000 N	Basic static load rating, radial
$C_{ur}$	6.300 N	Fatigue load limit, radial
$n_G$	10.200 1/min	Limiting speed
$n_G$ Grease	6.100 1/min	Limiting speed for grease lubrication
$n_{gr}$	7.300 1/min	Reference speed
$\approx m$	44,895 g	Weight

## Dimensions

$C_1$	26 mm	Width, outer ring
$r_{min}$	0,8 mm	Minimum chamfer dimension








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

### Additional information

SD25X32X4	Sealing ring
G25X32X4	Sealing ring 2
LR20X25X26,5	Suitable inner rings LR
IR20X25X26,5-XL	Suitable inner rings IR

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope