

**HK3520-2RS-AS3-L271** [↗](#)

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end  
HK...-2RS-AS3, single row, with cage

## Technical information

**Your current product variant**

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	AS3	With (3)
Coating	Without	
Sealing	2RS	Contact seal on both sides

**Main Dimensions & Performance Data**

$F_w$	35 mm	Under roller diameter
$D$	42 mm	Outside diameter
$C_r$	18.700 N	Basic dynamic load rating, radial
$C_{0r}$	33.500 N	Basic static load rating, radial
$C_{ur}$	4.450 N	Fatigue load limit, radial
$n_G$	4.500 1/min	Limiting speed
$n_G$ Grease	4.500 1/min	Limiting speed for grease lubrication
$\approx m$	40 g	Weight

**Dimensions**

$C_1$	20 mm	Width, outer ring
$r_{min}$	0,8 mm	Minimum chamfer dimension

**Temperature range**

$T_{min}$	-20 °C	Operating temperature min.
$T_{max}$	100 °C	Operating temperature max.



View product details on medias

18.06.2026, 04:58:41 UTC

SCHAEFFLER

### Additional information

---

LR30X35X20,5

Suitable inner rings LR

IR30X35X20-XL

Suitable inner rings IR