

**HK2526-AS1**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end  
HK...AS1, single row, with cage

## Technical information

**Your current product variant**

Lubricant	Without	
Lubrication hole	AS1	With (1)
Coating	Without	
Sealing	Without	

**Main Dimensions & Performance Data**

$F_w$	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	26 mm	Width
$C_r$	25.500 N	Basic dynamic load rating, radial
$C_{0r}$	45.000 N	Basic static load rating, radial
$C_{ur}$	6.300 N	Fatigue load limit, radial
$n_G$	10.200 1/min	Limiting speed
$n_G$ Grease	6.100 1/min	Limiting speed for grease lubrication
$n_{gr}$	7.300 1/min	Reference speed
$\approx m$	43,36 g	Weight

**Dimensions**

$C_1$	26 mm	Width, outer ring
$r_{min}$	0,8 mm	Minimum chamfer dimension







### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

### Additional information

SD25X32X4	Sealing ring
G25X32X4	Sealing ring 2
LR20X25X26,5	Suitable inner rings LR
IR20X25X26,5-XL	Suitable inner rings IR

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Small design envelope