

**HK0912**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Technical information



Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	9 mm	Under roller diameter
D	13 mm	Outside diameter
C	12 mm	Width
C_r	5.300 N	Basic dynamic load rating, radial
C_{0r}	6.300 N	Basic static load rating, radial
C_{ur}	870 N	Fatigue load limit, radial
n_G	26.500 1/min	Limiting speed
$n_{G \text{ Grease}}$	16.000 1/min	Limiting speed for grease lubrication
n_{gr}	20.200 1/min	Reference speed
$\approx m$	4,22 g	Weight

Dimensions

C_1	12 mm	Width, outer ring
r_{min}	0,4 mm	Minimum chamfer dimension



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	140 °C	Operating temperature max.

Additional information

GR9X13X3	Sealing ring
G9X13X3	Sealing ring 2
IR6X9X12-XL	Suitable inner rings IR

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope