

**HK1210**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Technical information



Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	12 mm	Under roller diameter
D	16 mm	Outside diameter
C	10 mm	Width
C_r	4.950 N	Basic dynamic load rating, radial
C_{0r}	6.200 N	Basic static load rating, radial
C_{ur}	820 N	Fatigue load limit, radial
n_G	20.700 1/min	Limiting speed
n_G Grease	12.400 1/min	Limiting speed for grease lubrication
n_{gr}	15.700 1/min	Reference speed
$\approx m$	4,38 g	Weight

Dimensions

C_1	10 mm	Width, outer ring
r_{min}	0,4 mm	Minimum chamfer dimension








Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	140 °C	Operating temperature max.

Additional information

SD12X18X3	Sealing ring
G12X18X3	Sealing ring 2
LR8X12X10,5	Suitable inner rings LR
IR8X12X10,5-XL	Suitable inner rings IR

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope