

**HK2012**

## Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

## Technical information



## Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Type of Seal	Without

## Main Dimensions &amp; Performance Data

$F_w$	20 mm	Under roller diameter
D	26 mm	Outside diameter
C	12 mm	Width
$C_r$	8.600 N	Basic dynamic load rating, radial
$C_{0r}$	12.100 N	Basic static load rating, radial
$C_{ur}$	1.480 N	Fatigue load limit, radial
$n_G$	12.700 1/min	Limiting speed
$n_G$ Grease	7.600 1/min	Limiting speed for grease lubrication
$n_{gr}$	9.700 1/min	Reference speed
$\approx m$	13,99 g	Weight

## Dimensions

$C_1$	12 mm	Width, outer ring
$r_{min}$	0,8 mm	Minimum chamfer dimension








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

### Additional information

SD20X26X4	Sealing ring
G20X26X4	Sealing ring 2
IR15X20X13-XL	Suitable inner rings IR

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope